

# Do the world's most efficient LED

## Industry flood light

Variety combinations of power and lighting



- **For high temperature, moisture ambient**

Ambient temperature:  $-45^{\circ}\text{C} \sim 65^{\circ}\text{C}$

Ambient moisture: 10%-90%

Ingress protection: IP66

Corrosion resistant: WF2

Collision prevention: IK10

With shock resistance technologies, widely used in industry

- **High performance**

Driver efficacy: 93%

PF > 0.98

THD < 13%

### Specification

Luminous efficacy(6000K-6500K) : 110LPW

LED spec: 12200lm@120W,

22000lm@200W

44000lm@400W

System power: 130W, 215W, 430W

CRI: Warm White Ra>80, Neutral White Ra>70

PF: > 0.98

THD: < 13%

Input voltage: 120-277Vac, 50/60Hz

Work voltage: 36Vdc, 42Vdc, 48Vdc

CCT: 2800K-6500K

Protection: IP66, WF2, IK10

N.W.: 12KG, 16KG, 25KG

Material: Aluminum Alloy + Glass

Ambient temperature: -45° C ~ +65° C

Ambient moisture: 10% ~ 90%

©2015 Above Lights high efficient lighting solution & manufacturer

Website: [www.abovelights.eu](http://www.abovelights.eu)

Europe: Dorfstraße 3 D-93326 Abensberg, Germany

Tel.: +0049(0)9443-992720 Email: [cp@abovelights.eu](mailto:cp@abovelights.eu)

North America: 10606 Shoemaker Ave Santa Fe Springs, CA, USA

Tel.: +1 56-2307-2121 Email:

[peter@abovelights.com](mailto:peter@abovelights.com)

